



## MIDAS CTD+



Valeport applies its unique distributed processing technology to the MIDAS CTD+ (formerly known as the Model 606+), resulting in a multiparameter CTD that is essentially tailor made to suit each customer's requirements. The instrument is able to accept any combination of a range of industry standard sensors, giving calibrated data in both autonomous and real time operations. A choice of titanium or acetal construction makes it suitable for coastal or deep water operations, and the intuitive software allows a range of both simple and complex sampling regimes.

### Sensors

The MIDAS CTD+ is fitted with CTD sensors as standard, plus your choice of optional additional sensors, either remote or bulkhead mounted. The CTD+ can also operate with Valeport's water sampler system, described on a separate brochure.

Sensor	Type	Range	Accuracy	Resolution
Conductivity	Inductive Cell	0 - 80mS/cm	±0.01mS/cm	0.002mS/cm
Temperature	PRT	-5 to +35°C	±0.005°C	0.002°C
Pressure	Strain Gauge	Up to 600 Bar	±0.04%	0.005%
Pressure	Piezo-Resistive	Up to 600 Bar	±0.01%	0.001%
Turbidity	Seapoint STM	0 - 2000FTU	±2%	0.002%
DO	Clark Cell	0 - 16ml/l	±0.07ml/l	0.017ml/l
pH	Electrode	2 - 12	±0.05	0.01
ORP(Redox)	Electrode	±1500mV	±1mV	0.1mV
Chlorophyll	Fluorometer	0 - 150µg/l	±0.03µg/l	0.005%
PAR	LICOR	10,000µmol/s/m <sup>2</sup>	±1%	0.5µmol/s/m <sup>2</sup>

Other sensors also available - please consult Valeport.

### Data Acquisition.

The MIDAS CTD+ uses the concept of distributed processing, where each sensor has its own microprocessor controlling sampling and calibration of readings. Each of these is then controlled by a central processor, which issues global commands and handles all the data. This means that all data is sampled at precisely the same instant, giving superior quality profile data. It also allows additional sensor to be added or replaced in the field, without the need for factory recalibration.

- Continuous:** Regular output from all sensors at 1, 2, 4 or 8Hz.
- Burst:** Regular sampling pattern, where instrument takes a number of readings, then sleeps for a defined time.
- Trip/Profile:** Data is output as a chosen parameter changes by a set value, usually Pressure for profiling.
- Conditional:** Instrument sleeps until a selected parameter reaches a set value.
- Delay:** Instrument sleeps until predefined start time

### Memory

The MIDAS CTD+ is fitted with 16Mb solid state non-volatile FLASH memory. Total capacity depends on sampling mode; continuous & burst modes have a single time stamp at the start of the file, trip mode (profiling) stores a time stamp with each reading. Each parameter uses 2 bytes per sample and a time stamp uses 7 bytes. The examples are for an instrument measuring CTD and 3 other parameters.

- Continuous:** ~1,400,000 data points
- Profile:** >850,000 data points (60 profiles to 6000m).

### Electrical

- Internal:** 8 x D cells, 1.5v alkaline or 3.6v lithium
- External:** 9 - 30vDC
- Power:** 1.7W (sampling), <1mW (sleeping)
- Battery Life:** >100 hours operation (alkaline)  
>250 hours operation (lithium)
- Connector:** Subconn Titanium MCBH10F

### Communications

The instrument will operate autonomously, with setup and data extraction performed by direct communications with PC before and after deployment. It also operates in real time, with a choice of communication protocols for a variety of cable lengths, some fitted as standard and selected by pin choice on the output connector:

#### Standard

- RS232** Up to 200m cable, direct to serial port.
- RS485** Up to 1000m cable, addressable half duplex comms
- RS422** Up to 1500m cable, addressable full duplex comms

#### Options

- FSK** 2 wire power & comms up to ~3500m cable (maximum cable length depends on cable specification - consult Valeport for confirmation)
- USB** For rapid upload or laptops without serial port
- Baud Rate:** 2400 - 115200 (FSK fixed at 19200, USB 460800)
- Protocol:** 8 data bits, 1 stop bit, No parity, No flow control

### Physical

- Materials:** Titanium or acetal housing, polyurethane & acetal sensor components, stainless steel cage
- Depth Rating:** 6000m (Titanium), 500m (acetal)
- Instrument Size:** 150mmØ x 590mm long
- Weight:** 15kg (titanium), 9kg (acetal)
- Shipping:** 860 x 530 x 310mm, 31kg (titanium), 25kg (acetal)

### Software

System supplied with DataLog 400 Windows based PC software, for instrument setup, data extraction and display. DataLog 400 is licence free.

### Ordering

- 0606002 MIDAS CTD+ (specify titanium or acetal), supplied with 3m communications lead, software, manual and transit case.
- 0400021 Turbidity sensor
- 0400017 DO Sensor
- 0400018 pH Sensor
- 0400019 Redox (ORP) Sensor
- 0400023 Chlorophyll Fluorometer
- 0400025 PAR Sensor

As part of our policy of continuing development, we reserve the right to alter at any time, without notice, all specifications, designs, prices and conditions of supply of all equipment.

Datasheet Reference Number: MIDAS CTD+ v1A