



## MONITOR SVP



The MONITOR SVP has been developed from Valeport's world leading MIDAS SVP, utilising the exceptional digital time of flight sound velocity sensor and synchronised sampling technique, but packaged as a smaller, lightweight unit to suit small boat or shallow water applications.

### Sensors

The MONITOR SVP is fitted with Valeport's digital time of flight sound velocity sensor, a fast response PRT temperature sensor, and strain gauge pressure transducer.

#### Sound Velocity

*Range:* 1400 - 1600m/s (extended range on request)

*Resolution:* 0.001m/s

*Accuracy:*  $\pm 0.06$ m/s

#### Temperature

*Range:* -5°C to +35°C

*Resolution:* 0.005°C

*Accuracy:*  $\pm 0.01$ °C

#### Pressure

*Range:* 50 Bar standard, others available

*Resolution:* 0.005% range

*Accuracy:*  $\pm 0.1$ % range

### Data Acquisition

The MONITOR SVP uses the concept of distributed processing, where each sensor has its own microprocessor controlling sampling and calibration of readings. Each of these is then controlled by a central processor, which issues global commands and handles all the data. This means that all data is sampled at precisely the same instant, giving superior quality profile data.

#### Sampling Modes

*Continuous:* Regular output from all sensors at 1, 2, 4 or 8Hz.

*Burst:* Regular sampling pattern, where instrument takes a number of readings, then sleeps for a defined time.

*Trip/Profile:* Data is output as a chosen parameter changes by a set value, usually Pressure for profiling.

*Conditional:* Instrument sleeps until a selected parameter reaches a set value.

*Delay:* Instrument sleeps until predefined start time

### Communications

The instrument will operate autonomously, with setup and data extraction performed by direct communications with PC before and after deployment. It also operates in real time, with a choice of communication protocols for a variety of cable lengths, all fitted as standard and selected by pin choice on the output connector:

#### Standard

*RS232* Up to 200m cable, direct to serial port.

*RS485* Up to 1000m cable, addressable half duplex comms

*RS422* Up to 1500m cable, addressable full duplex comms

#### Options

*USB* For rapid upload or laptops without serial port

*Baud Rate:* 2400 - 115200 (USB 460800)

*Protocol:* 8 data bits, 1 stop bit, No parity, No flow control

### Electrical

*Internal:* 8 x C cells, 1.5v alkaline or 3.6v lithium

*External:* 9 - 30vDC

*Power:* 0.6W (sampling), <1mW (sleeping)

*Battery Life:* <100 hours operation (alkaline)  
<250 hours operation (lithium)

*Connector:* Subconn MCBH10F

### Memory

The MONITOR SVP is fitted with 16Mb solid state non-volatile FLASH memory. Total capacity depends on sampling mode; continuous & burst modes have a single time stamp at the start of the file, trip mode (profiling) stores a time stamp with each reading. A single line of SVP data uses 8 bytes, and a time stamp uses 7 bytes.

*Continuous:* >1,000,000 data points

*Profile:* >500,000 data points (>500 profiles to 500m).

### Physical

*Materials:* Acetal housing, polycarbonate & composite sensor components, stainless steel (316) cage

*Depth Rating:* 500m

*Instrument Size:* 88mm $\varnothing$  x 540mm long

*Cage Size:* 640 x 140 x 120mm

*Weight (in cage):* 7.5kg (in air), 4.5kg (in water)

*Shipping:* 160 x 460 x 1020mm, 25kg

### Software

System supplied with DataLog Express Windows based PC software, for instrument setup, data extraction and display. DataLog Express is licence free.

### Ordering

0650008	MONITOR SVP Sound Velocity Profiler, supplied with deployment cage, 3m communications lead, DataLog Express software, manual and transit case.
0400002	16 Mbyte memory upgrade (max 64 Mbyte)
0400029	RS485 communications adaptor
0400030	RS422 communications adaptor
0400050	USB data upload lead

As part of our policy of continuing development, we reserve the right to alter at any time, without notice, all specifications, designs, prices and conditions of supply of all equipment.

Datasheet Reference Number: MONITOR SVP v1B